Accessible Parking Spaces

If parking spaces are provided for self-parking by employees or visitors, or both, then accessible spaces complying with the Americans with Disabilities Act Standards for Accessible Design (ADASAD) 502 shall be provided in each such parking area. Spaces need not be provided in the particular lot. They may be provided in a different location if equivalent or greater accessibility, in terms of distance from an accessible entrance and convenience is ensured.

Questions


Requirements

	1	
Space requirements (accessible and van accessible)	Yes No	Parking and Drop off A see ADASAD 502, 3 an
Are accessible spaces at least 96" wide with 60" wide access aisles?		Features of Accessible
Are van accessible spaces at least 132" wide with 60" wide access aisles?		
Is there at least 98" of vertical clearance along the route to and from the van space as well as over the van space and access aisle?	Indicate Vertical	
Is the surface of the space and access route firm and stable?		96 min
Are parking spaces and access aisles level with each other and have a surface slope not exceeding 1:48 (2.08%) in all directions?		त्र ₂₄₄₀ त (a) car
Are the access aisles part of the accessible route to the accessible entrance?		Access aisle for Parkin
Are the accessible spaces on the shortest accessible route of travel to the accessible entrance?		
Are spaces and aisles designated with blue li	nes?	ull length of parking space
Number requirements		
Are an appropriate number of accessible parking spaces available? (See table at right.)) $\mathbf{Yes} \mathbf{No}$	
Note: At least 1 of every 6 accessible spaces are to be van accessible.	<u> </u>	<u>60 r</u> 152
	No. of No. of	
Sign requirements	Spaces Accessible Spaces	Number of Spaces and
Are the vertical signs marked with the International Symbol of Accessibility?		Total SpacesAccessible1-251 space26-502 spaces51-753 spaces
Are there signs reading "Van Accessible" at van accessible spaces?		76-100 4 spaces 101-150 5 spaces 151-200 6 spaces
Are the signs located vertically, at least 60 inches from the bottom edge of the sign to the pavement?		201-300 7 spaces 301-400 8 spaces 401-500 9 spaces 501-1000 2% of total 1001+ 20+1 for ea


Indicate Height

Areas – for the complete rule, d Indiana Code 5-16-9

Parking Spaces:



g Spaces:



Signage:

